

AD-A260 607



DTIC
S ELECTE D
c
FEB 24 1993

AD

AD-E402 368

Technical Report ARAED-TR-92023

**MICROWAVE ABSORPTION MEASUREMENTS AND INTERFERENCE
EFFECTS FOR A LIQUID FUEL BETWEEN 2.5 and 18 GHz**

D. A. Wiegand
ARDEC

F. Murray
General Dynamics, Pomona Division
Pomona, CA

February 1993



U.S. ARMY
ARMAMENT RESEARCH,
DEVELOPMENT AND
ENGINEERING CENTER

**U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND
ENGINEERING CENTER**

Armament Engineering Directorate

Picatinny Arsenal, New Jersey

Approved for public release; distribution is unlimited.

93-03806



93 2 23 050

The views, opinions, and/or findings contained in this report are those of the authors(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement by or approval of the U.S. Government.

Destroy this report when no longer needed by any method that will prevent disclosure of its contents or reconstruction of the document. Do not return to the originator.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operation and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE Feb 1993		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE MICROWAVE ABSORPTION MEASUREMENTS AND INTERFERENCE EFFECTS FOR A LIQUID FUEL BETWEEN 2.5 AND 18 GHz			5. FUNDING NUMB	
6. AUTHOR(S) Donald A. Wiegand and Frank Murray				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESSES(S) ARDEC, AED Energetics and Warheads Div (SMCAR-AEE-WW) Picatinny Arsenal, NJ 07806-5000			8. PERFORMING ORGANIZATION REPORT NUMBER Technical Report ARAED-TR-92023	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(S) ARDEC, IMD STINFO Branch (SMCAR-IMI-I) Picatinny Arsenal, NJ 07806-5000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The incident, reflected and transmitted powers were measured and the reflection and transmission coefficients calculated for a liquid fuel. Two sizes of double-ridge waveguide were used to cover the frequency ranges 2.5 to 7.5 and 7.5 to 18 GHz and corrections were made for waveguide losses. Strong interference effects were observed and the real part of the dielectric constant was obtained primarily from the separation of interference maxima and minima. The loss tangent was obtained by curve fitting to the normalized power loss, and the absorption coefficient was calculated as a function of frequency from the dielectric data.				
14. SUBJECT TERMS Microwave, Reflection coefficient, Transmission coefficient, Absorption coefficient, Dielectric constant, dielectric loss, Loss tangent, Real part of dielectric constant, Imaginary part of dielectric constant, Complex dielectric constant.			15. NUMBER OF PAGES 19	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

CONTENTS

	Page
Background	1
Results and Discussion	3
Summary	5
References	9
Distribution List	11

DTIC QUALITY INSPECTED 3

Accession For	
NTIS CRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

BACKGROUND

The objective of this work was to survey a number of liquid fuels and hazardous materials (explosives, propellants, and pyrotechnics) to determine if there is significant absorption over a reasonably wide region of the microwave spectrum. The emphasis was placed on obtaining a measure of the absorption coefficients as a function of frequency and not on high accuracy or precision. The results for one liquid fuel are presented here. The procedure was to determine the in-waveguide reflection and transmission coefficients as a function of frequency from the measured incident, reflected, and transmitted powers after correction for waveguide and other losses. The complex dielectric constant was obtained from these coefficients and the absorption coefficient calculated.

Measurements were made over the frequency range 2.5 to 18 GHz by the use of two sizes of double-ridge waveguide to cover the ranges 2.5 to 7.5 and 7.5 to 18 GHz. Step scanning at 0.1 and 0.25 GHz intervals was used for the low frequency range and the high frequency range respectively, and the incident, reflected, and transmitted powers were recorded at each frequency. A complete description of the apparatus is given elsewhere (refs 1 and 2). The sample cell consisted of a vertical waveguide section 30.45 cm (12 in.) in length bounded on the bottom by a thin (0.0076 cm) mylar support window for the liquid fuel. The top of the cell was connected to the microwave source by means of a bidirectional coupler for measurements of the incident and reflected powers, P_i and P_r , while the bottom of the cell was connected to an identical coupler for measurement of the transmitted power, P_t . This coupler was terminated in its characteristic impedance. The thin mylar support window was placed across the waveguide normal to the propagation direction and sandwiched between the waveguide section used for the sample holder and the bidirectional coupler used to measure the transmitted intensity. Therefore, the mylar support window interrupted the continuity of the waveguide. All powers were corrected for waveguide and other losses and calibration differences (refs 1 and 2). By conservation of energy

$$P_i = P_r + P_t + P_{ab} \quad (1)$$

where P_{ab} is the power absorbed at the sample and cell. By division of equation (1) by P_i

$$1 = R + T + A \quad (2)$$

where $R = P_r/P_i$ and $T = P_t/P_i$ are the power reflection and transmission coefficients and

$$A = P_{ab}/P_i = 1 - (R + T) \quad (3)$$

is the normalized absorbed power.

Expressions for the power reflection and transmission coefficients, R and T , for normal incidence on a plane parallel slab of dielectric in air in a waveguide were derived using the techniques given by Ramo and Whinnery (ref 3). These are

$$R = r_{12}^2 [e^{2\alpha d} + e^{-2\alpha d} - 2\cos(2\beta d)] / [e^{2\alpha d} + r_{12}^4 e^{-2\alpha d} - 2r_{12}^2 \cos(2\phi_{12} - 2\beta d)] \quad (4)$$

and

$$T = t_{12}^2 t_{21}^2 / [e^{2\alpha d} + r_{12}^4 e^{-2\alpha d} - 2r_{12}^2 \cos(2\phi_{12} - 2\beta d)] \quad (5)$$

where d is the dielectric slab thickness in the direction of propagation and

$$\rho_{12} = r_{12} \theta \phi_{12} = (Z_2 - Z_1) / (Z_2 + Z_1) \quad (6)$$

$$\tau_{12} = t_{12} \theta \phi_{12} = 2Z_2 / (Z_2 + Z_1) \quad (7)$$

$$\tau_{21} = t_{21} \theta \phi_{12} = 2Z_1 / (Z_2 + Z_1) \quad (8)$$

$$\alpha = 2\pi f (\mu_0 \epsilon_0 \epsilon' / 2)^{1/2} \{1 - (f_c/f)^2 / \epsilon'\}^{1/2} \{1 + [(\epsilon''/\epsilon')^2 / \{1 - (f_c/f)^2 / \epsilon'\}^2]^{1/2} - 1\}^{1/2} \quad (9)$$

and

$$\beta = 2\pi/\lambda = 2\pi f (\mu_0 \epsilon_0 \epsilon' / 2)^{1/2} \{1 - (f_c/f)^2 / \epsilon'\}^{1/2} \{1 + [(\epsilon''/\epsilon')^2 / \{1 - (f_c/f)^2 / \epsilon'\}^2]^{1/2} + 1\}^{1/2} \quad (10)$$

ϵ' and ϵ'' are the real and imaginary parts of the complex dielectric constant; μ_0 and ϵ_0 are the permeability and permittivity of vacuum (air); f_c is the waveguide cutoff frequency in air; and λ is the wavelength in the waveguide in the dielectric (ref 3). Equations 4 and 5 are valid when the waveguide section after the sample (bidirectional coupler) is terminated in its characteristic impedance so that there is no reflected wave in this section. Z_1 and Z_2 are the in-waveguide impedances of vacuum (air) and the dielectric, respectively, and are given by

$$Z_1 = (\mu_0/\epsilon_0)^{1/2} [1 - (f_c/f)^2]^{1/2} \quad (11)$$

$$Z_2 = (\mu_0/\epsilon_0 \epsilon')^{1/2} [1 - j\epsilon''/\epsilon'] [1 - (f_c/f)^2 / \epsilon']^{1/2} \quad (12)$$

ρ_{12} and τ_{12} are the field reflection and transmission coefficients for normal incidence on the dielectric slab when conditions are such that there is no reflected wave in the dielectric. τ_{21} is the similar transmission coefficient for a wave in the dielectric incident on air. α and β are the real and imaginary parts of the complex field propagation constant in the dielectric defined by

$$E = E_0 e^{-(\alpha - j\beta)z} \quad (13)$$

where z is the distance in the direction of propagation. α is therefore the field attenuation or absorption coefficient, and β is 2π times the reciprocal wave length (eq 10), both in the dielectric slab. Born and Wolf give relationships similar to equations 4 and 5 for out-of-waveguide conditions (ref 4).

Significant simplifications of the above equations are possible for low-loss materials, i.e., when $\epsilon''/\epsilon' \ll 1$. This is the case for the liquid fuel under considerations and the appropriate approximations were made in the calculations of R and T .

RESULTS AND DISCUSSION

Measurements have been made on two liquid fuels, liquid water, eight hazardous materials, and two polymeric materials, but because of space limitations, only the results for one liquid fuel (Diesel 2) are presented here. The results for liquid water and the other materials will be published elsewhere (ref 1).

Measurements were made of P_i , P_r , and P_t for the empty cell and the reflection and transmission coefficients calculated. Typical reflection coefficient results are given in figure 1a for the low frequency range. Similar results were obtained for the high frequency range. The peaks in the reflection coefficient spectra are due to the discontinuity in the waveguide caused by the thin mylar support window. This was verified by measurements for the empty waveguide, i.e., without the mylar and by measurements for plastic samples which were machined to fit snugly into the waveguide and so used without the mylar. Calculations were also made of the reflection coefficients for the mylar alone. These calculations indicate that the reflection coefficient for the thickness of mylar used is negligible over the whole frequency range used for these studies. Peaks of this type were also found in the reflection and transmission spectra for liquid samples in the cell (fig. 1b). No attempt is made here to correct the results for these peaks due to the discontinuity in the waveguide. However, in fitting the calculated reflection and transmission coefficients to the experimental coefficients allowance was made for the effects of the discontinuity.

The experimentally determined reflection coefficient for the fuel Diesel 2 is given as a function of frequency in figure 1b for the low frequency range. Somewhat similar results were obtained for the high frequency range (not shown). The maxima and minima are due to interference effects and the change in wavelength with frequency. The effect of the mylar window and so the discontinuity in the waveguide on the reflection coefficient of the sample can be clearly seen by a comparison of figures 1a and 1b. Large peaks in the reflection coefficient of the sample in the cell occur at approximately the same frequencies as the peaks in the reflection coefficient of the empty cell.

Also shown in figure 1b is the calculated reflection coefficient with ϵ' and ϵ''/ϵ' chosen as a function of frequency so that the differences between the calculated and experimental reflection and transmission coefficients are minimized. The mylar window and the discontinuity are not considered in the calculations. However, calculations which were made for the sample and the mylar but without the discontinuity indicate that the mylar alone has negligible effect on the total reflection coefficient. Measurements were made every 0.1 GHz, and the calculated reflection coefficient of figure 1b is also given for comparison purposes only at every 0.1 GHz at the same frequencies as those used in the measurements.

An examination of figure 1b indicates excellent agreement between the frequencies of the maxima and minima of the experimental and calculated reflection coefficients. In addition, the amplitudes of the experimental and theoretical coefficients are in rather good agreement except at frequencies corresponding to the frequencies of the peaks of the empty cell as given in figure 1a. The initial value of ϵ' was estimated from the separation of the maxima and minima and was then adjusted as a function of frequency to obtain the best match between the positions of the maxima and minima of the experimental and theoretical reflection coefficients (ref 1)

The transmission coefficient data and calculations are not presented. ϵ''/ϵ' was determined by using the normalized absorbed power, A, of equation 3. The calculated values of A were adjusted to the experimental values for the sample at selected frequencies by the choice of ϵ''/ϵ' at each frequency. A polynomial was then fitted to the values of ϵ''/ϵ' versus frequency and used to calculate A as a function of frequency. The final values of ϵ' and ϵ''/ϵ' at each frequency were selected to minimize the differences between the experimental and theoretical values of R and A.

ϵ' was found to decrease with increasing frequency between 2.5 and approximately 8.5 GHz and then to remain constant between 8.5 and 18 GHz within experimental error. ϵ''/ϵ' was found to decrease with increasing frequency over most of

the frequency range but to plateau at about 15 GHz with indications of an increase with further increases in frequency. These results indicate that there is a relaxation process giving a maximum of absorption at a frequency below the frequency range of measurement and further that there is another relaxation process with an absorption maximum above the frequency range of measurement. The dielectric constant results will be discussed in detail elsewhere (ref 1).

The out-of-waveguide absorption coefficient for Diesel 2 was calculated using equation 9 with $f_c = 0$ and the experimentally determined values of ϵ' and ϵ''/ϵ' and is given in figure 2. This coefficient increases with frequency throughout the range of measurement and is small.

SUMMARY

Measurements were made of the in-waveguide incident, reflected and transmitted powers of liquid fuel between 2.5 and 18 GHz, corrections were made for waveguide and other system losses, and reflection and transmission coefficients calculated. The reflection and transmission coefficients indicate strong interference effects. Expressions were obtained for the in-waveguide theoretical reflection and transmission coefficients in terms of the complex dielectric constant, the waveguide cutoff frequency, and the sample thickness. The real part of the dielectric constant was then chosen as a function of frequency so that the maxima and minima of the calculated reflection spectrum matched those of the experimental spectrum and further minimized the differences between the two reflection spectra. The loss tangent was chosen as a function of frequency so as to match the calculated normalized power loss to the experimental values. The out-of-waveguide absorption coefficient was then obtained as a function of frequency from these results. The absorption coefficient is small and increases with frequency.




Figure 1. (a) Measured reflection coefficient of the empty sample cell.
 (b) Measured reflection coefficient of the sample (Diesel 2 fuel) and cell and the calculated reflection coefficient of the sample.




Figure 2. Absorption coefficient versus frequency for Diesel 2 fuel

REFERENCES

1. Wiegand, D. A. and Murray, F., "The Complex Dielectric Constants and Absorption Coefficients of Liquid Hydrocarbon Fuels Between 2.5 and 19.0 GHz," to be published.
2. Murray, F., Helling, G., Wiegand, D. A., and Pinto, J., "Susceptibility of Energetic Materials and Fuels to High Power Microwaves," Proceedings of the Fifth National Conference on High Power Microwave Technology, edited by F. A. Brown, R. Kaul, and L. Libelo, published by Science and Technology Corp, Hampton, VA, 1990, pp 481-484.
3. Ramo, S. and Whinnery, J. R., Fields and Waves in Modern Radio, 2nd ed., John Wiley & Sons Publisher, New York, 1964, Cpt 7 and 9.
4. Born, M. and Wolf, E. Principles of Optics, Pergamon Press, New York, 1959, p 627.

DISTRIBUTION LIST

Commander

Armament Research, Development and Engineering Center

U.S. Army Armament, Munitions and Chemical Command

ATTN: SMCAR-IMI-I (5)

SMCAR-TD, T. Davidson

SMCAR-AE, B. Bushey

G. R. Taylor

P. Marinkas

F. Cotton

SMCAR-AEE-WW, D.A. Wiegand (25)

J. Pinto

B. Fishburn

M. Mezger

Y. Lanzerotti

SMCAR-AEE-W, M. Kirshenbaum

N. Slagg

SMCAR-AES, S. Kaplowitz

SMCAR-AEE, J. Lannon

SMCAR-AEE-B, D. Downs

SMCAR-AEE-BP, S.B. Bernstein

SMCAR-AEE-BR, E. Costa

SMCAR-CCH-V, F. Hildebrant

SMCAR-AEE-BR, T. Beardell

SMCAR-AET-M, A. Rupel

S. Cytron

SMCAR-FSM, G. Lutz

T. Jarnes

SMCAR-FSP, D. Panhorst

G. Schwartz

Picatinny Arsenal, NJ 07806-5000

Commander

U.S. Army Armament, Munitions and Chemical Command

ATTN: AMSMC-GCL (D)

AMSMC-QAR-R, L. Manole

E. Bixon

Picatinny Arsenal, NJ 07806-5000

Administrator
Defense Technical Information Center
ATTN: Accessions Division (12)
Cameron Station
Alexandria, VA 22304-6145

Director
U.S. Army Material Systems Analysis Activity
ATTN: AMXSY-MP
AMXSY-D
Aberdeen Proving Ground, MD 21005-5066

Commander
Chemical Research, Development and Engineering Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCCR-MSI
Aberdeen Proving Ground, MD 21010-5423

Commander
Chemical Research, Development and Engineering Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCCR-RSP-A
Aberdeen Proving Ground, MD 21010-5423

Director
Ballistic Research Laboratory
ATTN: AMXBR-OD-ST
AMXBR-BLT, R. Frey
AMXBR-BLC, J. Starkenberg
AMXBR-BLT, P. Howe
AMXBR-TBT, R. Lieb
H. Roehelio
Aberdeen Proving Ground, MD 21005-5066

Chief
Benet Weapons Laboratory, CCAC
Armament Research, Development and Engineering Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCAR-CCB-TL
SMCAR-LCB-RA, J. Vasilakis
Watervliet, NY 12189-5000

Director
U.S. Army TRADOC Systems Analysis Activity
ATTN: ATAA-SL
White Sands Missile Range, NM 88002

Office of the Secretary of Defense
OUSD(A)
Director, Live Fire Testing
ATTN: James F. O'Bryon
Washington, DC 20301-3110

Director
U.S. Army Aviation Research and Technology Activity
Ames Research Center
Moffett Field, CA 94035-1099

Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-CS-R (DOC)
 AMSMI-RD-DE, Gordon T. Lill, Jr.
 AMSMI-RD-DE-UB, Buford Jennings
Redstone Arsenal, AL 35898-5010

HQDA (SARD-TR)
Washington, DC 20310-0001

Commander
U.S. Army Tank Automotive Command
ATTN: AMSTA-TSL, Technical Library
Warren, MI 48397-5000

Commander
U.S. Army Materiel Command
ATTN: AMCDRA-ST
5001 Eisenhower Avenue
Alexandria, VA 22333-0001

Commander
U.S. Army Laboratory Command
ATTN: AMSLC-DL
Adelphi, MD 20783-1145

Commandant
U.S. Army Infantry School
ATTN: ATSH-CD-CSO-OR
Fort Benning, GA 31905-5066

Air Force Armament Laboratory
ATTN: AFATL/DLODL
Eglin Air Force Base, FL 32542-5000

Air Force Armament Technology Laboratory
ATTN: AFATL/DOIL
AFAT/DLODL
Eglin Air Force Base, FL 32542-5438

Commander
U.S. Rock Island Arsenal
ATTN: SMCAR-TL, Technical Library
AMSMC-ESM(R), W. D. Fortune
AMSMC-IRD, G. H. Cowan
Rock Island, IL 61299-5000

Commander
U.S. Army Aviation Systems Command
ATTN: AMSAV-DACL
4300 Goodfellow Blvd
St. Louis, MO 63120-1798

Commander
U.S. Army Research Office
ATTN: Chemistry Division
P.O. Box 12211
Research Triangle Park, NC 27709-2211

Commander
Naval Surface Warfare Center
ATTN: R10C, L. Roslund
R10B, M. Stosz
Silver Spring, MD 20902-5000

Commander
Naval Surface Warfare Center
ATTN: R13, J. Short
R. Bernecker
J. Forbes
Silver Spring, MD 20902-5000

Commander
Naval Weapons Center
ATTN: L. Smith
A. Amster
R. Reed, Jr.
China Lake, CA 93555

Commander
Ballistic Missile Defense Advanced Technology Center
ATTN: D. Sayles
P.O. Box 1500
Huntsville, AL 35807

Air Force Rocket Propulsion Laboratory
ATTN: AFRPL-MKPA
Edwards Air Force Base, CA 93523

Southwest Research Institute
ATTN: M. Cowperthwaite
H. J. Gryting
6220 Culebra Road
Postal Drawer 28510
San Antonio, TX 78284

New Mexico Institute of Mining and Technology
ATTN: TERA, T. Joyner
Campus Station
Socorro, NM 87801

Director
Lawrence Livermore National Laboratory
ATTN: R. McGuire
K. Scribner
E. Lee
M.S. Costantino, L-324
M. Finger
Livermore, CA 94550

Director
Los Alamos National Laboratory
ATTN: J960, J. Ramsay
P.O. Box 1663
Los Alamos, NM 87545

Director
Sandia National Laboratory
ATTN: J. Kennedy
Albuquerque, NM 87115

Honeywell, Inc.
ATTN: R. Tompkins
10400 Yellow Circle Drive
MN 3803300
Minnetonka, MN 55343

Johns Hopkins University
Applied Physics Laboratory
Chemical Propulsion Information Agency
ATTN: John Hannum
Johns Hopkins Road
Laurel, MD 20707

Morton Thiokol, Inc.
Louisiana Division
ATTN: Lee C. Estabrook
P.O. Box 30058
Shreveport, LA 71130

Commander
Naval Weapons Station
ATTN: L. Rothstein, Code 50 - NEDED
Yorktown, VA 23491

John Dienes
Los Alamos National Laboratory
ATTN: MS B221
MS P952
MS H811, R. Hoerberling
Los Alamos, NM 87545

Commander
Naval Surface Warfare Center
ATTN: Code F45, Robert E. Richardson
Therese Houghton
Code H202, R. Amadori
Dahlgren, VA 22448

Director
U.S. Laboratory Command, VLAMO
ATTN: AMSLC-VL-DE, Richard Reitz
Aberdeen Proving Ground, MD 21005-5001

Air Force Systems Command
ATTN: AFSC/XTW, LTC W. Dugan
AFSC/XTHO, LTC Garrett Polhemus
Andrews Air Force Base, MD 20334

Lawrence Livermore National Laboratory
ATTN: L86, Hriar Cabayan
L153, Richard Zacharias
P.O. Box 5504
Livermore, CA 94550

Lawrence Livermore National Laboratory
ATTN: L153, Michael Bland
P.O. Box 808
Livermore, CA 94551

Commander
Harry Diamond Laboratories
ATTN: SLCHD-HPM, E. Brown
David Bassett
SLCHD-TA, Edward Sebol
SLCHD-NW-CS, Roger Kaul
2800 Powder Mill Road
Adelphi, MD 20783-1145

Commander
Air Force Weapons Laboratory
ATTN: WL/AWS, LTC Michael Starch
HPM Program Manager, Major Rex Schlicher
WL/TALP, CPT David Knight
Richard Scholfield
CPT Alex Pilipowsky
Richard Copeland
Kirtland Air Force Base, New Mexico 87117-6008

Commander
Belvoir Research Development and Engineering Center
ATTN: STRBE-NAD, James Owen
Herman Spitzer
Chris Wanner
Sigberto Garcia
Fort Belvoir, VA 22060-5605

U.S. Naval Research Laboratories
ATTN: CODE 4650, Terence Wieting
Washington, DC 20375-5000

Commander
Eglin Air Force Base
ATTN: AFATL-MNF, Robert Erhart
Eglin Air Force Base, FL 32542-5434

SRD, FANX-III
ATTN: Ralph Hitchesn, Room B5E32
Fort Meade, MD 20755